



# SCANTEAM<sup>®</sup> 5700 Series

## High Performance Hand Held Laser Scanner

The SCANTEAM 5700 Hand Held Laser Scanner is Hand Held Products' high performance laser. It combines our best laser scanning performance with Hand Held Products' traditionally excellent decoding, interfacing, and product durability reputation. The 5700 is available with a full suite of decoded output interfaces or non decoded output for connection to an external decoder or portable terminal.

Hand Held Products laser scanners are comfortable to use, rugged, durable, and easy to program. They offer a wide selection of cables, upgradable Flash memory, and Quick\*Load, a Windows<sup>®</sup>-based programming tool, to maximize flexibility.

The 5700 is a high performance scanner suitable for any general purpose application. It offers the widest range of resolution and reading distance of any Hand Held Products scanner. The 5700 finds application in retail point of sale, factory and office automation, inventory, asset tracking, and transportation uses. It also offers Dual Interface - with a simple cable change, the scanner automatically switches interfaces (such as from retail POS to portable data collection), increasing functionality and cost effectiveness.

### Features & Benefits

#### **Excellent Scanning Performance**

*Reads down to 5 mil codes. Working distance up to 31 inches.*

#### **Auto Scanning**

*Hands free scanning option for faster throughput.*

#### **Dual Interfaces**

*A simple cable change automatically allows one scanner to be used on two terminal interfaces.*

#### **Flash Memory**

*Field upgradable memory extends the useful life of the product.*

#### **Rugged Design**

*Durable products that survive in the real world.*

#### **Common Architecture**

*Common interfaces, cables, and programming with Quick\*Load.*

#### **Two Year Warranty**

*Full factory warranty, plus world wide service and support.*

## Performance

**Scan Element:** Mylar resonant scan element  
**Light Source:** 650nm visible laser diode (VLD)  
**Laser Power:** .8 mW ± 10%  
**Scan Rate:** 36 scans per second  
**Field Width:** 3.4 in. (8.6cm) at 4.5 in. and 20 in. (50.8cm) at 31 in.



<b>Working Distance:</b>	<b>5mil</b>	<b>7.5 mil</b>	<b>10 mil</b>	<b>20 mil</b>	<b>55mil</b>
	2.5 in. - 3.5 in. (6.35cm - 8.89cm)	2 in. - 7.0 in. (5.08cm - 17.78cm)	1 in. - 10 in. (2.54cm - 25.4cm)	1.5 - 18 in. (3.81cm - 45.72cm)	4 - 31 in. (10.16cm - 78.74cm)

**Print Contrast:** 25% MRD  
**Skew Angle:** ± 65° minimum from normal  
**Pitch Angle:** ± 55° minimum from normal

## Mechanical/Electrical

### Dimensions

**Weight:** 7 oz. (198g)  
**Length:** 5.8 in. (14.8cm)  
**Width:** 3 in. ( 7.5 cm)  
**Laser Classification:** CDRH Class II

### Power Requirements

**Voltage:** Non-Decoded Output +4.5 to 5.5 VDC  
Decoded Output: +5VDC or +12VDC, depending on interface

<b>Current:</b>	<b>Product</b>	<b>Idle</b>	<b>Scanning</b>
	5700/A-00	Less than .06 mA	110mA
	5700/A-01	100mA*	200mA
	5700/A-02	70mA*	170mA max
	5700/A-03	90mA*	190mA

\*When operated in switched power mode, idle current is less than 0.06mA.

### Environmental

**Ambient Light:** Sunlight: 8000 ft. candles  
**Temperature Ranges**  
**Operating:** 32°F to 122°F (-0°C to 50°C)  
**Storage:** -40°F to 140°F (-40°C to 60°C)  
**Humidity:** 5% to 95% (non-condensing)  
**Shock:** Five 5 ft. (1.5m) drops to a concrete surface  
**Agency Conformance:** FCC Class B CE

**MIL Spec w/Scanboot:** MIL-STD-810E, 506.3, #2, Drip  
MIL-STD-810E, 510.3, #1, Wind Blown Dust

**Electrostatic Discharge:** 15kv to any external surface

**Symbologies:** UPC-EO, E1, A; EAN; JAN; ISBN all versions with supplement suppression; Codes 3 of 9; 128; I 2 of 5; 2 of 5; Matrix 2 of 5; 11; 93; MSI; Plessey; and Codabar



Complies with EMC 89/336/EEC and LVD 73/23/EEC

Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 • Email info@opal.ch • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opalsa.ch • Germany • OPAL Associates GmbH • Lohnerhof-Str. 2 • D-78467 Konstanz • Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opalgmbh.de • OPAL Associates GmbH • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email hamburg@opalgmbh.de • Austria • OPAL Associates GesmbH • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opalgmbh.at

