

STATIONARY TERMINALTrakker® Antares™ **T248X****Benefits:**

- **Compact, industrial design**
- **Robust data collection**
- **Flexible, open connectivity**
- **Rapid application development**



The Trakker Antares Stationary Terminal delivers timely, accurate data for mission critical manufacturing systems. With a compact metal case, environmental sealing and power protection, the reliable T248X handles the most punishing industrial plants. It's ideal for work in process tracking, labor collection, and time and attendance applications.

The T248X Stationary Terminal includes two ports for bar code input devices and a serial port to connect a printer or scale. An optional integrated badge scanner, digital input/output and two additional serial ports accommodate the most demanding data collection requirements.

Choose Ethernet, wireless or serial connections to host computers. With the 2.4 GHz wireless models, you can easily change configurations of manufacturing work cells. The T248X supports client/server and terminal emulation host environments. It's also compatible with Intermec CrossBar® networks.

The Trakker Antares Stationary Terminal is programmable using industry standard, Microsoft® C. With EZBuilder™, Intermec's rapid application development tool, you can dramatically reduce development time and cost for creating shop floor solutions.

Trakker® Antares™ **T248X****Enclosure**

Die cast aluminum case
NEMA5/IP53 sealing for dust, moisture and splashing

Physical Characteristics

Height: 24.4 cm (9.6")
Length: 27.2 cm (10.7"); 28.7 cm (11.3") with badge scanner
Depth: 9.9 cm (3.9")
Weight: 4.3 kg (9.5 lbs)

Displays

CGA compatible LCD with backlight
T2480/85: 4 lines by 40 characters per line
T2481/86: 12 lines by 40 characters per line Display up to 24 lines

Keypads

Alphanumeric: 59 key elastomeric; PC style layout; 5 separate function keys
Oversized function/numeric: 35 key elastomeric; 10 separate function keys
Time and Attendance: 35 key membrane, 10 separate function keys
Terminal Emulation: IBM 5250, IBM 3270 and ANSL/VT

Input Ports

2 bar code input ports
Digital input/output: 4 optically isolated sense inputs; 4 two form C output relays, dry contacts
External speaker connection

Power

Operating: 95 - 250 volts AC, 50/60 Hz
Power protection: Handles 1 second dropouts
Memory Backup: Rechargeable NiCad battery pack

Bar Codes Supported

Code 39, 2 of 5, Interleaved 2 of 5, Codabar, UPC/EAN, Code 128, Code 11, Code 93 and 93i, Plessey, MSI, Code 16K, Code 49, PDF-417 and Code 1 supported using Intermec Janus 7010 Imager

Development Environment

Microsoft® C and Trakker Antares Programmer's Software Kit
EZBuilder, rapid application development

Memory

RAM: 1MB Total, 512K available to user
Non-volatile memory: 2MB (operating firmware, configuration data, application and data storage), 750K available to user
Extended Memory: 2MB Flash; 2MB or 4MB SRAM

Wired Data Communication

Ethernet: 10BaseT
Serial Ports: RS-232, RS-232/422/485
Intermec Crossbar

Wireless Data Communication

T2485/86
Frequency Band: 2.4 GHz. Frequency range varies by country
Radio Type: WLI Forum OpenAir™ Frequency Hopping Spread Spectrum
Radio Power Output: 100 mW
Radio Data Rate: 1.6 Mbps per channel, 800 Kbps fallback rate for extended range
Channels: Supports 15 independent, non-interfering "virtual channels"
Protocols: TCP/IP and UDP Plus
Security: 20 digit security IDs customer selectable

Environment

Operating temperature: -20° to 50°C (-4° to 122°F)
Storage temperature: -20° to 60°C (-4° to 140°F)
Humidity: Non-condensing (0 to 95% RH)

Badge Scanner

Visible light badge scanner
Infrared light badge scanner

Host Support Direct Connect

Host Environment: IBMAS/400, S/390, Digital, HP, UNIX with Telnet Services
Connectivity: Ethernet, 2.4 GHz wireless, serial
Communication: TCP/IP, XMODEM/ YMODEM
Terminal Emulation: TN 5250, TN 3270, VT/ANSI

Host Support DCS 300

Host Environment: IBMAS/400, S/390, Digital, HP, UNIX
Connectivity: 10/100 Mbps Ethernet, Token Ring, Twinax, Coax, SDLC
Communications: TCP/IP, SNA, TCP/IP socket pass through
Terminal Emulation: IBM SNA 5250, 3270, ANSL/VT 100, 220, 320, and Screen Mapping

Language Support

English, German, French, Italian, Spanish, Portuguese. Localized fonts, keypads and Getting Started Guide.
Supports additional single and double byte fonts. Font edit and download tool.
Display and scan western European characters in terminal emulation

Accessories

Wall or desk mount brackets, Programmer's Software Kit, EZBuilder, Adapter for third serial port (9 pin RS-232)

Regulatory Approvals

UL Listed, UL 1950 and C22.2 No. 950, TUV Rheinland GS, EN 60950, FCC Part 15, Canada, RSS210 and ICES 003 Class B, EN 55022/CISPR 22, Class B, ETS 300 826, ETS 300 328, Compliant with European Directives CE Marked

North America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax • Norand Mobile Systems Division • 550 2nd Street S.E. • Cedar Rapids, Iowa 52401 • 1 (800) 452-2757 tel • 1 (319) 369-3453 fax • Amtech Systems Division • 19111 Dallas Parkway, Suite 300 • Dallas, Texas 75287-3106 • 1 (800) 923-4824 toll-free • 1 (972) 733-6600 tel • 1 (972) 733-6699 fax

Europe/Middle East/Africa • Sovereign House • Vastern Road • Reading, Berkshire, RG1 8BT • United Kingdom • +44 118 987 9400 tel • +44 118 987 9401 fax

Asia Pacific/Latin America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax

Label Products and Supplies • North America • 1 (513) 874-5882 tel • 1 (513) 874-8487 fax • or 1 (800) 227-9947 tel • 1 (800) 227-1707 fax • Latin America/Asia Pacific • 1 (513) 870-7930 Int'l phone • 1 (513) 874-3613 Int'l fax • Europe/Middle East/Africa +31 24 372 3100 tel • +31 24 378 0070 fax

World-Wide Fax Document Retrieval Service • 1 (650) 556-8447 tel • 1 (800) 755-5505 (North America Only)

Internet • www.intermec.com **E-mail** • info@intermec.com

Copyright © 1998 Intermec Technologies Corporation. All rights reserved. All trademarks are the property of their respective owners. Contents subject to change. Printed in the U.S.A. 608322B 7/98

**Where
Information
Gets Down
To Business™**

Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 • Email info@opal.ch • **OPAL Associates SA** • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opalsa.ch • **Germany** • OPAL Associates GmbH • Löhnerhofstr. 2 • D-78467 Konstanz • Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opalgmbh.de • **OPAL Associates GmbH** • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email hamburg@opalgmbh.de • **Austria** • OPAL Associates GmbH • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opalgmbh.at

