

**DIRECT THERMAL/
THERMAL TRANSFER
PRINTER**

EasyCoder™ **3600**

Benefits:

- **Ideal for Compliance Labeling**
The 3600 is ideal for industry standard label formats requiring a 6" label, such as AIAG labels
- **Value-Priced Printer**
Affordability in the 6" printer segment makes the highly reliable 3600 the printer of choice for all your general purpose labeling requirements.
- **Numerous Options**
Satisfy your application requirements with many connectivity and printer options not normally offered on value-priced printers.
- **Built to Last**
Heavy-duty metal casing is perfect for today's dynamic warehouse, distribution and manufacturing environments.



Featuring Intermec's renowned industrial design, 6" print width and 203 dpi resolution, the 3600 is suitable for today's bar code label standards. Printing bar codes in 5 mil increments, makes the 3600 ideal for a variety of 4" and 6" compliance shipping and container labels, such as AIAG, ODETTE and EAN-128. Printing large text for applications requiring maximum readability such as chemical drum or pallet labeling is easy using the large outline font included on 3600. User-defined, downloadable fonts are also supported for further label design flexibility.

The 3600 features several options you might not expect on a value priced printer. For starters, Label Auto-Peel is

included as a standard feature on the 3600. The Auto-Peel feature peels the label away from the liner and presents the label to the operator for easier and faster labeling. If batch labeling is required, the printer can be outfitted with an internal batch take-up adapter.

Host connectivity options are enhanced with support for IBM Twinax & Coax environments. Optional Centronics parallel interface is available for high speed communications.

High quality design and long-lasting performance - it all adds up to the solid reputation that organizations worldwide have come to trust from the industry's leading manufacturer.

EasyCoder™ 3600

General

Direct Thermal and Thermal Transfer Printer for high volume wide self-adhesive label, ticket and tag applications. Internal rewind and auto-peel.

Model

EasyCoder 3600

Physical Characteristics

Length: 44 cm (17.25")

Height: 27.7 cm (10.9")

Width: 30.5 cm (12")

Weight: 20.4 kg (45 lbs.)

Print Specifications

Element: 0.125 mm (0.00492")

Maximum Length: Unlimited

Maximum Width: 168 mm (6.6")

"X" Dimension: 0.13 to 1.27 mm (5 to 50 mil)

Speed: 51, 77, 102 or 127 mm/sec (Select 2", 3", 4" or 5"/sec)

Resolution: 8 dots/mm (203 dpi)

Media Specifications

Roll: 152 m (6000" linear)

Roll Dimensions: 213 mm (8.38")

Width: 76 to 170 mm (3 to 6.7")

Thickness: .08 to .3 mm (0.003 to 0.012")

Core size: 76 mm (3")

Ribbon Specifications –

Roll: 152 m (6000" linear)

Widths: 77, 104, 137, & 170 mm (3", 4.1", 5.4", & 6.7")

Standard Features

Auto-Peel with liner take up

Digital thermal compensation—dot-by-dot—electronics for excellent print quality, even for rotated bar codes

Compatible with Intermec's printer family and supports 86XX printers in emulation mode

Industrial design with enclosed label supply

128K NVRAM for permanent storage of downloaded fonts, graphics, and label formats

Communications

Rate: 1,200 to 19,200 bps

Flow Control: XON/XOFF, ready/busy

Asynchronous: RS-232-C, RS-422, RS-485

Fonts and Graphics

21 resident bit-mapped fonts (includes OCR-A and OCR-B)

Outline font

Supports user-defined fonts and graphics

Language

IPL is an advanced printer programming language that includes many features not available in other bar code printers

Advanced bar code algorithms handle all required encodation

Error detection protocols verify secure data transmission

Command errors and printer status are easily identified to your host

Communicates in printable ASCII or control characters

Independent character and field rotation

Connectivity

Serial interface standard

Centronics Parallel interface optional

Internal Ethernet interface optional

Internal IBM Twinax or Coax interface optional

Microsoft® Windows

Intermec InterDriver™ standard Windows 3.x, 9x, NT 4.0/5.0

Intermec ActiveX® controls standard Windows 9x, NT 4.0/5.0

PrintSet™ printer configuration utility Windows 3.x, 9x, NT4.0/5.0

NetPilot™ + Thin Wizard™ network configuration utility (with optional Ethernet) Windows 9x, Windows NT 4.0/5.0

Character Sets

Code page 850, French, German, ISO 256 character, Italian, Kanji/Katakana (optional), Norwegian/Danish, Spanish, Swedish/Finnish, Swiss, UK ASCII, USA ASCII

Power Supply

100, 115, 200 and 230 V AC +10%; 50 Hz to 60 Hz

Environment

Operating Temperature: 4° to 40°C (41° to 104°F)

Storage Temperature: 0° to 70°C (32° to 120°F)

Humidity: Non-condensing (10 to 90%)

Bar Code Symbolologies

Code 2 of 5, Code 11, Code 39, Code 93, Code 128, Codabar, HIBC, Interleaved 2 of 5, Postnet, UPC/EAN, JIS-ITF

2D: Code One, Code 16K, Code 49, DataMatrix, MaxiCode, PDF417

Standards Supported Partial Listing

AIAG Primary Metals; AIAG B-10; EIA (shipping container); LOGMARS; MITL; ODETTE; TCIF (shipping label); UCC/EAN 128 Serial Shipping Container; UPC/EAN Shipping Container

Regulatory Approvals

CSA certified (C22.2 No. 950-M89) 115V; ICES-003 Class B 115V; EC EN 55022 (CISPR22) Class B ; 100V, 200V, 230V; FCC Part 15, Class B 115V; FTZ VFG 243/1992; TÜV GS licensed; (IEC 950 & EN 60950) 230V; UL® listed (1950) 100V, 115V, 200V; Compliant with all relevant EU directives

Options

Memory expansion to 512K NVRAM; Bitmap and outline Kanji/Katakana; RF Gateway (902-928 MHz)

Internet • www.intermec.com **E-mail** • info@intermec.com **Telephone** • 800-347-2636 (toll free in N. Am.) **Service and Support** • 800-755-5505 (toll free in N. Am.)

North America

Headquarters • 6001 36th Avenue West, Everett, WA 98203-9280, tel: 800-347-2636 (toll free in N. Am.), fax: 661-775-4440
Norand Mobile Systems Division • 550 2nd Street S.E., Cedar Rapids IA 52401, tel: 800-452-2757 (toll free in N. Am.), fax: 319-369-3453
Amtech Systems Division • 1911 Dallas Parkway, Suite 300, Dallas, TX 75287-3106, tel: 800-923-4824 (toll free in N. Am.), fax: 972-733-6699
Label Products & Supplies • tel: 800-227-9947 (toll free), 513-874-5882 (direct), fax: 800-227-1707 (toll free), 513-874-8487 (direct)

Europe / Middle East & Africa

Sovereign House, Vastern Road, Reading, Berkshire, RG1 8BT United Kingdom, tel: 44-118-987-9400, fax: 44-118-987-9401

Asia Pacific/ Latin America

Hong Kong • 26-12 Shell Tower, Times Square, 1 Matheson Street, Causeway Bay, tel: 852-2574-9777, fax: 852-2574-9725
Singapore • #25-16 International Plaza, 10 Anson Road, 079903, tel: 65-324-8391, fax: 65-324-8393
Australia • 15 Stamford Road, Oakleigh Victoria 3166, tel: 61-3-9563-0000, fax: 61-3-9563-4000
South America and Mexico • 2572 White Road, Irvine, CA 92614, tel: 949-975-1905 Ext. 1939, fax: 949-975-1827

Worldwide Fax Document Retrieval Service • tel: 800-755-5505 (toll free in North America), 650-556-8447 (direct)

Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 • Email info@opal.ch • **OPAL Associates SA** • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opalsa.ch • **Germany** • OPAL Associates GmbH • Lohnerhofstr. 2 • D-78467 Konstanz • Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opalgmbh.de • **OPAL Associates GmbH** • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email hamburg@opalgmbh.de • **Austria** • OPAL Associates GesmbH • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5223 58833 • Telefax +43 (0)5223 521569 • Email info@opalgmbh.at

