

“UCAT” HEAVY-DUTY LABEL UNWINDERS

A label unwinder is what you need to manage your label supply rolls. From very inexpensive to very sophisticated, LABELMATE's new family of Heavy-Duty “UCAT” Label Unwinders will keep your label production running smoothly. All LABELMATE Unwinders are bi-directional.

New! UCAT-S: This unwinder is unpowered, and has fixed brake. It's the world's least expensive professional Unwinder. The UCAT-S accepts up to 30-cm diameter rolls and up to 16-cm width, 76-mm cores (other core sizes are available).


UCAT-1: This is the classic LABELMATE Unwinder with Adjustable Speed-Proportional Braking. 30-cm diameter rolls and 16-cm width, 76-mm cores (other core sizes are available). Optional 25-cm width, 40-cm roll diameter and a 25- to 101-mm Adjustable Core Holder are available.

New! UCAT-2 (CAT-2 with Tension Arm): This powered Unwinder automatically tracks label usage and provides powered label feed at speeds up to 75 cm/sec. The UCAT-2 accepts standard 76 mm cores and rolls up to 30 cm in diameter (other core sizes available). 25 cm width is available. It can also be used as a full-featured Label Rewinder without any special setup. LABELMATE's renowned Constant Adjustable Torque™ control system allows precise adjustment of feed speeds and rewind torque. External STOP / RUN Input included.

New! UCAT-40: A powered Unwinder like the UCAT-2, but with an impressive 40 cm (16”) roll diameter capacity. Supplied with LABELMATE's new “Quick Chuck”™, the UCAT-40 gives you the ultimate label unwinder for volume production.

All LABELMATE Products are industrial-quality, maintenance-free, and backed by a 3-Year Parts and Labor Limited Warranty, the longest in the industry. Order a LABELMATE UCAT Unwinder to solve your label supply roll problems today.

“UCAT” LABEL UNWINDERS



The new UCAT-S



The new UCAT-2


The new UCAT-40



MODEL	DESCRIPTION	LABEL WIDTH	ROLL DIAM.	MAX. SPEED
<i>New!</i> UCAT-S	Unwinder with no brake. For 76 mm cores.	Up to 16 cm	Up to 30 cm	N/A
UCAT-1	Heavy-duty Label Unwinder for label rolls with 76 mm core. Continuously adjustable Speed Proportional Frictionless Braking™.	Up to 16 cm	Up to 30 cm	Up to 75 cm/sec
UCAT-1-W9	UCAT-1 for labels up to 25 cm wide.	Up to 25 cm	Up to 30 cm	Up to 75 cm/sec
UCAT-1-R16	UCAT-1 with 40 cm roll diameter.	Up to 16 cm	Up to 40 cm	Up to 75 cm/sec
UCAT-1-ACH	UCAT-1 with Adjustable Core Holder for 25 to 101 mm diameter cores.	Up to 16 cm	Up to 30 cm	Up to 75 cm/sec
<i>New!</i> UCAT-2	Heavy-duty Powered Label Unwinder for label rolls with 76 mm cores. Continuously adjustable feed rate. Control arm tracks label unwind usage automatically.	Up to 16 cm (25 cm with Option W9)	Up to 30 cm	Up to 75 cm/sec
<i>New!</i> UCAT-2-W9	UCAT-2 for labels up to 25 cm wide.	Up to 25 cm	Up to 30 cm	Up to 75 cm/sec
<i>New!</i> UCAT-1-CH	UCAT-1 Unwinder with “Quick Chuck”™	Up to 17 cm	Up to 30 cm	Up to 75 cm/sec
<i>New!</i> UCAT-2-ACH	UCAT-2 with Adjustable Core Holder for 25 to 101 mm diameter cores.	Up to 16 cm	Up to 30 cm	Up to 75 cm/sec
<i>New!</i> UCAT-40	Heavy-duty Powered Unwinder with “Quick Chuck”™. Continuously adjustable feed rate. Control arm tracks label unwind usage automatically.	Up to 17 cm	Up to 40 cm	Up to 75 cm/sec

Base plate footprint: 180 x 280 or 370 mm **Weight:** 9kg to 13kg.

Power Requirements: UCAT-S & UCAT-1 No power required. Others: 120/240vac 50-60Hz 50va. max.



UCAT-1 / UCAT-S

UCAT-1-W9

UCAT-2

UCAT-1-ACH / UCAT-2-