

Falcon[®] 4220

Windows[®] CE .NET PDA



Features:

- Intel[®] XScale™ PXA255 400MHz
- Windows CE .NET Operating System
- Choice of Laser or LRCCD Scanning Options
- Optional Handle for Scan Intensive Applications
- Open Architecture – SDIO and CF slot for RF, Memory, etc.
- 802.11b Cisco Compatible Wireless LAN
- Bluetooth for wireless printing and communications
- GPRS WWAN for field applications

The Falcon[®] 4220 is PSC's latest generation PDA device, combining a compact, ruggedized form factor with the flexibility of Microsoft's CE .NET operating system. The Falcon 4220 is designed for retail, logistics, and field force automation applications where maximum performance and durability is required in a compact handheld device.

Performance is Power

Under the hood, the Falcon 4220 uses cutting edge technologies from the leaders in mobile and wireless technology, such as Microsoft, Intel, Cisco and others. The Falcon 4220 features the Intel[®] XScale™ PXA255 400MHz processor and the Microsoft™ Windows CE .NET operating system, providing you with the power and flexibility to deploy sophisticated mobile applications in your enterprise.

The Intel XScale processor provides you with the highest performing mobile processor available today along with advanced power management capabilities for extended battery life. Microsoft's Windows CE .NET operating system gives you the freedom to select the software solution that best meets your needs. This architecture provides all the power you need to run multiple applications, Voice over IP (VoIP), and even voice recognition in the future.

Rugged Yet Versatile

The Falcon 4220 is designed from the ground up for rugged applications. With its IP54 sealing, 4 foot (1.2m) repeated drops to concrete, and wide operating temperature range, the Falcon 4220 stands up to most any demanding application.

A Stunning Display

The Falcon 4220 incorporates the latest technology in Color TFT displays. With its super-bright, high contrast display, the 4220 works as well outdoors as it does inside. The integrated touchscreen allows for pen/touch based input and handwriting recognition.

Communications, Communications, Communications

The Falcon 4220 integrates the 3 leading wireless technologies in one device. Featuring 802.11b WLAN, Bluetooth, and GPRS WWAN, the 4220 can communicate wherever your mobile worker requires.



Specifications

Falcon® 4220

Mechanical

Dimensions

Length: 6.6" / 16.8 cm

Width: 3.1" / 7.8 cm

Height: 1.3" / 3.3 cm

Weight

With battery 12.7 oz / 360 g

Without battery 11.1 oz / 315 g

Display

3.5" / 8.9 cm 240 x 320 graphic, transfective TFT

256,000 colors

Sunlight readable (for outdoor use)

Keypad

17 plus 4-way navigation

Construction

Industrial, high-strength polycarbonate/
ABS-blend plastic

Environmental

Temperature rating

Operating: 14° to 122° F / -10° to 50° C

Storage: -4° to 140° F / -20° to 60° C

Humidity: 5 to 95% NC

Shock: multiple 4.0' / 1.2m drops to concrete

Water & Dust: IEC529 rating IP54

Vibration: Exceeds MIL STD 810F

Optical

Light source:

Laser: 650nm VLD

Scan rate:

39 scans/second nominal

Depth of Field: see chart below

Indicators:

One triple-color LED for ALARM notification (R)
and charger indicator (G/B)

One dual-color LED for scanner indicator

Ambient light immunity

Standard

Artificial light: 450 ft-candles /4,844 lux

Sunlight: 10,000 ft-candles /107,639 lux

Decoding Capability *(autodiscriminates between)*

ID Scan Engine

Code 39

Code 39 Extended

Interleaved 2 of 5

EAN8, 13, 128

UPC-A

UPC-E

Code 128

Code 93

Codabar

Chinese Postage Code IATA

MSI/Plessey

Code 32

STD 2 of 5

Code 11

Matrix 2 of 5

Safety and Regulatory

Electrical: Complies to CE

Emissions: FCC Part 15 - Class A, CISPR B

Laser classification: CDRH Class II;

(CAUTION: Laser Radiation –

do not stare into beam);

IEC 60825 Class 2



Cradle

Spare battery charging slot

USB host and client interface

Standard RS232 communication

Ethernet module ready (optional)

Depth-of-Field Chart –

(printing resolution, contrast and ambient light dependent;

* Minimum distance determined by symbol length and scan angle)

Label Density	Typical Range	
5 mil	2.2" to 5.0"	5.6 to 12.7 cm
7.5 mil	1.8" to 7.5"	4.6 to 19.1 cm
10 mil	2.0" to 9.7"	5.1 to 24.6 cm
13 mil	2.0" to 12.0"	5.1 to 30.5 cm
20 mil	* to 15.0"	* to 38.1 cm
40 mil	* to 22.0"	* to 55.9 cm
55 mil	* to 29.0"	* to 73.7 cm

System

Operating System

Windows® CE .NET 4.2

Microprocessor

Intel® XScale™ PXA255

Memory

64MB flash ROM

64MB SDRAM

Communication Ports

Infrared: One IrDA 1.2 compliant port

Serial: RS232 via optional cable or cradle

USB: Supports USB v1.1 both host and client (dock and terminal)

I/O Slots

One SDIO card slot

One Compact Flash Type II slot (3.3V)

Audio

One mono speaker

2.5mm DIA stereo earphone jack with
microphone input (headset)

Power Options

1800mAh Li-Polymer removable/rechargeable battery.

Optional 2700mAh hour battery

25mAh rechargeable backup battery (Holds system
data at least 2 hours without main battery)

AC adapter with 100-240 Vac, 50-60Hz

Support for Xscale application modes including:

Turbo Mode, Normal Mode, Idle Mode, Sleep Mode

Peripheral power - On/Off controllable via software

Radio Support

Cisco compatible 802.11b

System Support

VT100/220, HP700/92, IBM 3270 & 5250

via PowerNet Twin Client™

Browser support via Microsoft® Internet Explorer

Wireless software distribution and terminal

configuration via Falcon Management Utility (FMU)

TCP/IP Communications

Development Environments

Many standard Windows CE development tools

(Embedded Visual C++, Visual C#, Visual Basic,

.NET, Personal Java 1.1)

Java Virtual Machine (JVM)

Falcon® CE Developers Toolkit

Wavelink Studio

PSC Inc.

959 Terry Street

Eugene, OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140

Specifications are subject to change without notice.

Additional information concerning this product or other PSC products

and services can be found at the PSC website: www.pscnet.com,

or contact your PSC representative for more information.



Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)1 931 12 22 • Telefax +41 (0)1 931 12 20 •
Email info@opal-holding.com • URL <http://www.opal.ch/> • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 •
Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opal-holding.com • URL <http://www.opalsa.ch/> •
Germany • OPAL Associates GmbH • Lohnerhofstrasse 2 • D-78467 Konstanz Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 •
Email info@opal-holding.com • URL <http://www.opalgmbh.de/> • OPAL Associates GmbH • Osterholder Allee 2 • 25421 Pinneberg •
Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email info@opal-holding.com • OPAL Solutions GmbH • Wilhelmstr. 22 • 52428 Jülich •
Telefon +49 (0)2461 936 770 • Telefax +49(0)2461 936 771 • Email info@opal-holding.com • URL <http://www.opal-solutions.de/> •
Austria • OPAL Associates GesmbH • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 523 58833 • Telefax +43 (0)523 521569 •
Email info@opal-holding.com • URL <http://www.opalgmbh.at/>

