

PowerScan® 2D Imager

Industrial Strength Imaging Scanner



Mechanical

Dimensions: 2.7 x 4.4 x 7.2" (6.9 x 11.2 x 18.3 cm)

Weight: 9.6 oz. (272 g) without cable

Electrical

Operating voltage: 4 VDC to 14 VDC

Operating Current (maximum)

Interlaced Aiming: 275 mA @ 5V

Concurrent Aiming: 450 mA @ 5 V

Standby Current (maximum)

Normal Mode: 60 mA @ 5.5V

Low Power Mode: 30 mA @ 5.5V

Environmental

Temperature rating

Operating: 14° to 122° F (-10° to 50° C)

Storage: -40° to 158° F (-40° to 70° C)

Humidity: 5 to 95% NC

Shock: Withstands Multiple 6.5' (2 m) drops to concrete

Vibration: Meets MIL-STD-810E

Water & Dust: IEC529 Rating IP54DW

Optical

Light sources

Red Illumination LEDs: 626nm ± 30nm

Green Aiming LEDs: 520nm ± 30nm

Imager Resolution: VGA, 640 x 480 pixels

Pitch: ± 40°

Skew: ± 40°

Ambient Light Capability: 535 to 100,000 Lux

Depth of Field: See Depth of Field Table below

DEPTH OF FIELD
Typical Range Comparisons

LABEL DENSITY	SR MODELS	HD MODELS
75 mil Linear	—	15 - 55"/38 - 140 cm
8 mil Linear	2.5 - 6.6"/6.4 - 16.8 cm	—
13 mil UPC	1.5 - 11.5"/3.8 - 29.2 cm	1.3 - 7.9"/3.3 - 20.1 cm
6.6 Mil PDF417	3.5 - 5.3"/8.9 - 13.5 cm	1.8 - 5.0"/4.6 - 12.7 cm
15 mil Data Matrix	2.7 - 5.5"/6.9 - 15.0 cm	1.3 - 5.0"/3.3 - 12.7 cm
35 mil Maxi Code	1.0 - 12.0"/2.5 - 30.5 cm	1.0 - 9.0"/2.5 - 22.9 cm
Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.		

Decoding Capability

Linear

- Code 11
- Code 28
- UPC/EAN/JAN
- RSS
- Code 39
- Codabar
- Interleaved 2 of 5
- Many Others
- Code 93
- Code 2 of 5

2D

- PDF417
- MicroPDF
- Code 49
- Maxicode
- Data Matrix
- QR Code
- Aztec Mesas
- Aztec
- EAN-UCC
- Others
- Composites

Postal Codes

- Postnet
- China Post
- KIX
- Canadian Post
- Japanese Post
- Planet Code
- British Post
- Others

OCR

- OCR-A
- OCR-B
- Others

Host Communications RS232C and USB

Warranty 3 Years

Accessories

P/N: 7-0462	Universal Kit	P/N: 7-0430
P/N: 11-0070	Scan Stand	Take Up Reel
		Holster/Fork Lift Mount



Safety & Regulatory

Electrical: Complies to TÜV; UL; cUL

Emissions: Complies to FCC; EN 55022-B; CNS13438; AS/NZS 3548; VCCI



PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140

Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)44 931 12 22 • Telefax +41 (0)44 931 12 20 • Email info@opal-holding.com • URL <http://www.opal.ch/> • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opal-holding.com • URL <http://www.opalsa.ch/> • Germany • OPAL Associates GmbH • Löhnerhofstrasse 2 • D-78467 Konstanz • Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opal-holding.com • URL <http://www.opalgmbh.de/> • OPAL Associates GmbH • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email info@opal-holding.com • OPAL Associates GmbH • München • Telefon +49 (0)89 12737 556 • Telefax +49 (0)89 12737 557 • Email info@opal-holding.com • OPAL Associates GmbH • Frankfurt • Telefon +49 (0)69 8236 6501 • Telefax +49 (0)69 8236 7709 • Email info@opal-holding.com • OPAL Solutions GmbH • Wilhelmstr. 22 • 52428 Jülich • Telefon +49 (0)2461 936 770 • Telefax +49(0)2461 936 771 • Email info@opal-holding.com • URL <http://www.opal-solutions.de/> • Austria • OPAL Associates GesmbH • Vorarlberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opal-holding.com • URL <http://www.opalgmbh.at/> • OPAL Associates GesmbH • Donauefelderstr. 101/2/8 • 1210 Wien • Telefon +43 (0)1 270 03 13 • Telefax +43(0)1 270 03 15 • Email info@opalgmbh.at

