

PowerScan® PDF Imager

Industrial Strength Imaging Scanner



Mechanical

Dimensions: 2.7 x 4.4 x 7.2" (6.9 x 11.2 x 18.3 cm)

Weight: 9.6 oz. (272 g) without cable

Electrical

Operating Voltage: 4 VDC to 14 VDC

Operating Current (maximum)

Interlaced Aiming: 275 mA @ 5V

Concurrent Aiming: 450 mA @ 5 V

Standby Current (maximum)

Normal Mode: 60 mA @ 5.5V

Low Power Mode: 30 mA @ 5.5V

Environmental

Temperature Rating

Operating: 14° to 122° F (-10° to 50° C)

Storage: -40° to 158° F (-40° to 70° C)

Humidity: 5 to 95% NC

Shock: Withstands Multiple 6.5' (2 m) drops to concrete

Vibration: Meets MIL-STD-810E

Water & Dust: IEC529 rating IP54DW

Optical

Light sources

Red Illumination LEDs: 626nm ± 30nm

Green Aiming LEDs: 520nm ± 30nm

Imager Resolution: VGA, 640 x 480 pixels

Pitch: ± 40°

Skew: ± 40°

Ambient light capability: 535 to 100,000 Lux

Depth of Field: See Depth of Field Table below



Ideal For:

- Warehousing
- Transportation & Logistics
- Package Distribution
- Electronic Assembly
- Heavy-Duty Manufacturing
- Retail

Features:

- Industry Leading Environmental Performance in shock/drop, sealing and temperature extremes
- High Performance Image Capture and Omni-directional, point-and-shoot label reading
- Ergonomic, Over-Molded Enclosure with integrated metal tether hook and cable retainer
- Bright Aiming Illumination to Ensure Fast, reliable scanning in diverse lighting conditions
- Flexible Mounting and Storage Accessories Available
- Durable, Solid State Scanning Backed by an Industry Leading three year Warranty

DEPTH OF FIELD Typical Range Comparisons

LABEL DENSITY	SR MODELS	HD MODELS
75 mil Linear	—	15 - 55"/3.8 - 14.0 cm
8 mil Linear	2.5 - 66"/6.4 - 16.8 cm	—
13 mil UPC	1.5 - 115"/3.8 - 29.2 cm	1.3 - 7.9"/3.3 - 20.1 cm
6.6 Mil PDF417	3.5 - 53"/8.9 - 13.5 cm	1.8 - 5.0"/4.6 - 12.7 cm
10 mil PDF417	2.1 - 8.0"/5.3 - 20.3 cm	1.2 - 6.6"/3.0 - 16.8 cm
Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.		



PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140

Switzerland • OPAL Associates AG • Motorenstrasse 116 • CH-8620 Wetzikon • Telefon +41 (0)44 931 12 22 • Telefax +41 (0)44 931 12 20 • Email info@opal-holding.com • URL <http://www.opal.ch/> • OPAL Associates SA • Avenue des Boveresses 54 • Case postale 29 • CH 1000 Lausanne 21 • Telefon +41 (0)21 653 95 00 • Telefax +41 (0)21 653 95 02 • Email info@opal-holding.com • URL <http://www.opalsa.ch/> • Germany • OPAL Associates GmbH • Löhnerhofstrasse 2 • D-78467 Konstanz • Telefon +49 (0)7531 813 000 • Telefax +49 (0)7531 813 00 99 • Email info@opal-holding.com • URL <http://www.opalgmbh.de/> • OPAL Associates GmbH • Osterholder Allee 2 • 25421 Pinneberg • Telefon +49 (0)4101 787 615 • Telefax +49(0)4101 787 616 • Email info@opal-holding.com • OPAL Associates GmbH • München • Telefon +49 (0)89 12737 556 • Telefax +49 (0)89 12737 557 • Email info@opal-holding.com • OPAL Associates GmbH • Frankfurt • Telefon +49 (0)69 8236 6501 • Telefax +49 (0)69 8236 7709 • Email info@opal-holding.com • OPAL Solutions GmbH • Wilhelmstr. 22 • 52428 Jülich • Telefon +49 (0)2461 936 770 • Telefax +49(0)2461 936 771 • Email info@opal-holding.com • URL <http://www.opal-solutions.de/> • Austria • OPAL Associates GesmbH • Voralberger Wirtschaftspark • A-6840 Götzis • Telefon +43 (0) 5523 58833 • Telefax +43 (0)5523 521569 • Email info@opal-holding.com • URL <http://www.opalgmbh.at/> • OPAL Associates GesmbH • Donaufelderstr. 101/2/8 • 1210 Wien • Telefon +43 (0)1 270 03 13 • Telefax +43(0)1 270 03 15 • Email info@opalgmbh.at

