

HITAG 2

125kHz RFID IC

Read-Write 256 bits

Features

- 256 bits EEPROM memory organized in 8 pages of 32 bits each
- 32 bits unique factory programmed serial number
- Typical operating frequency : 125kHz
- Contactless power supply, very low power (*I_{read}*=7μA_{max}, *I_{write}*=20μA_{max})
- Manchester or Biphase encoding type, data rate : 2 or 4 kBd
- Different operating mode :
 - Crypto Mode : encrypted data communication
 - Password Mode : Password check before writing or reading data
 - Public Mode A : Emulate Read Only 64 bit Manchester, 4kBd devices
 - Public Mode B : ISO compatible to the norm 11784/785
 - Public Mode C : Emulate the Philips family PIT PCF7930/31

Memory Organisation

	0	31
Page 0	Serial Number	Read Only
Page 1	Security data, configuration	Read/Write or Write protected or Read and Write protected
.		
.		
Page 3	User data	Read/Write or One Time Programmable
Page 4		
.		
Page 7		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

CLF 3.3.5.2	Version : 2	Validation : 01.10.2001	By : VMB
Public Use	Accomplishment : Final	Status : Released	DefKey : 6809

